



NF 29

MULTIFUNCTION METER

The unit is low cost, easy-to-use, individual and multifunctional that enables to measure all the basic parameters required in an electrical installation and monitors electricity over and above basic metering. The entire range is very rugged and cost-effective. All these products are field proven and more than 100,000 units are active in service.



FEATURES

- ✓ MULTIPARAMETER MONITORING
- ✓ MICRO-CONTROLLER BASED
- ✓ MEASUREMENT OF ALL IMPORTANT ELECTRICAL PARAMETERS
- ✓ ALL PARAMETERS WITH DEFAULT ACCURACY CLASS 1.0s
- ✓ DISPLAYS WITH CUSTOMIZED LCD
- ✓ INDIVIDUAL VOLTAGES AND CURRENTS FOR ALL THREE PHASES (R-Y-B)
- ✓ INDIVIDUAL THREE POWERS-KW, KVA AND KVAR
- ✓ INDIVIDUAL PF AND SYSTEM PF WITH LEAD (-) AND LAG SIDE
- ✓ COMPACT 96 X 96 X 65 MM DIN ENCLOSURE
- ✓ FREQUENCY (HZ), THREE ENERGIES (KWH, KVAH, KVARH)
- ✓ THD, VOLTAGE & CURRENT AVAILABLE (OPTIONAL)

DISPLAY PARAMETERS

- ✓ V, A, KWH, KVAH, KVARH, PF, Hz, System & Phase wise KW, KVA, KVAR.

TRINITY ENERGY SYSTEMS PVT LTD

386, Savli G.I.D.C. Industrial Estate, Nr. Manjusar, At & Po: Alindra, Tal.: Savli, Dist. Vadodara - 391775 Gujarat, INDIA
Phone: +91-922 800 4452/53/54, Email: info@trinityenergy.co.in | www.trinityenergy.co.in

TECHNICAL DATA

PARAMETERS		
Volts R-N	Direct Voltage Input : 20 to 300V L-N Burden : 0.5VA	
Volts Y-N		
Volts B-N		
Volts RY	Direct Voltage Input : Up to 500V L-L Burden : 0.5VA	
Volts YB		
Volts BR		
I R	Secondary Current : 5A or 1A (Site Selectable) Input CT Primary : Site Selectable Range of Reading : 5-5000A Burden : <1.0VA Overload : 5A CT=6A RMS Continuous 1A CT=1.2A RMS Continuous	
I Y		
I B		
Frequency	45 to 55 Hz, Accuracy: 0.3% of Reading	
KWh	Range of Reading: 0 to 9999999.9 KWh Accuracy : 1.0S as per IS13779.	
KVARh	Range of Reading: 0 to 9999999.9 KVARh Accuracy : 1.5% of Reading (Between 0.5 Lag to 0.8 Lead)	
KVAh	Range of Reading: 0 to 9999999.9 KVAh Accuracy : 1.0% of Reading	
System PF	Accuracy : 1% of Reading (IPFI>0.5) Range of Reading : 0.05 to 1.00 Lag/Lead	
System KVA	Accuracy : 1.0%of Reading	
System KW	Accuracy : 1.0%of Reading	
System KVAR	Accuracy: 1.5% of Reading (Between 0.5 Lag to 0.8 Lead)	
Display	Customized LCD	
Bezel	96x96mm	DINenclosure
Depth	65 mm	

